

DESIGNER™

Square Lay-in, Tegular coarse texture

UP TO **42%** RECYCLED CONTENT

Calculate LEED contribution at armstrong.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT



Designer™ Lay-in panels with Prelude® 15/16" suspension system (Pgs. 279-280)

Designer™ offers a coarse-textured visual with standard absorption in an economical ceiling panel.

KEY SELECTION ATTRIBUTES

- Standard sound absorption
- Cost-effective

TYPICAL APPLICATIONS

- Utility rooms
- Discount stores
- Supply and storage rooms

COLOR



White

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 295-299 armstrong.com/catdwgs	Item No.	Dimensions (Inches)
DESIGNER Square Lay-in			
15/16" Square Lay-in	1	735	24 x 24 x 5/8" <input type="checkbox"/>
	1	734	24 x 48 x 5/8" <input type="checkbox"/>
DESIGNER Tegular			
15/16" Angled Tegular	13	737	24 x 24 x 5/8" <input type="checkbox"/>


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics ¹	Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	Warranty
NRC	CAC										
0.55	30	-	Class A	0.81	-	Std	-	Std	Std	•	1-Yr
0.55	30	-	Class A	0.81	-	Std	-	Std	Std	•	1-Yr
0.55	33	-	Class A	0.81	-	Std	-	Std	Std	•	1-Yr

¹ Total Acoustics™ ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product.

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber

Surface Finish
Factory-applied latex paint

Fire Performance
Class A: Flame Spread Index 25 or less (UL labeled) per ASTM E1264

ASTM E1264 Classification
Type III, Form 2, Pattern F
Fire Class A

Humidity/Sag Resistance
Standard performance ceiling panels, adequate where the building is enclosed and the HVAC is continuously functioning.

Insulation Value
R Factor – 1.5 (BTU units)
R Factor – 0.26 (Watts units)

Warranty
Details at armstrong.com/warranty

Weight; Square Feet/Carton
734 – 0.80 lbs/SF; 80 SF/ctn
735, 737 – 0.80 lbs/SF; 64 SF/ctn

Minimum Order Quantity
1 carton

Metric Items Available
735M, 734M, 737M – Metric items are subject to extended lead times and minimum quantities. Contact your representative for more details.