

FINE FISSURED™

Tile
medium texture

56% RECYCLED CONTENT

Calculate LEED contribution at armstrong.com/greengenie

LEED®

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/extended producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

\$\$\$



Fine Fissured™ Tile with Prelude® Concealed 15/16" suspension system (Pg. 275)

Fine Fissured™ panels offer a non-directional visual, standard acoustics, and concealed or tongue-and-groove installation.

KEY SELECTION ATTRIBUTES

- 12" x 12" concealed tile option provides grid-hiding monolithic installation
- Non-directional visual reduces scrap and installation time
- 30-Year Limited System Warranty against visible sag, mold and mildew

TYPICAL APPLICATIONS

- Areas with low ceiling height or limited plenum

COLOR



White

VISUAL SELECTION

Edge Profile	Susp. Dwg. Pgs. 295-299 armstrong.com/ catdwgs	Item No.	Dimensions (Inches)
FINE FISSURED™ Tile			
Concealed	66	746	12 x 12 x 5/8" □
Tongue-and-Groove	63	741	12 x 12 x 1/2" □


PERFORMANCE SELECTION

Dots represent high level of performance.

UL Classified Acoustics		Total Acoustics ¹	Fire Rating	Light Reflect	Anti-Mold & Mildew	Sag Resist	Certified Low VOC Emissions	Durability	Recycled Content	Recycle Program	30-Yr Warranty
NRC +	CAC										
0.55	35	-	Class A	0.85	•	•	•	Std	•	•	•
0.55	N/A	-	Class A	0.85	•	•	•	Std	•	•	•

¹ Total Acoustics™ ceiling panels have an ideal combination of noise reduction and sound-blocking performance in one product. Splines not included in carton. Not recyclable when glue-up installation method is used.

SUSPENSION SYSTEM



STAPLE UP/ADHESIVE



PHYSICAL DATA

Material

Wet-formed mineral fiber

Surface Finish

Factory-applied latex paint

Fire Performance

ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled.)

ASTM E1264 Classification

Type III, Form 2, Pattern C E
Fire Class A

Humidity/Sag Resistance

HumiGuard® Plus ceiling panels maintain superior sag resistance. Recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew

Ceiling panels with BioBlock® coating contain a mold-inhibiting agent that resists the growth of mold and mildew.

VOC Emissions

Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.1, 2010. This standard is the guideline for low emissions in LEED, CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

High Recycled Content

Contains greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.

Insulation Value

R Factor – 1.6 (BTU units)
R Factor – 0.28 (Watts units)

30-Year Performance Guarantee & Warranty

When installed with Armstrong® Suspension System. Details at armstrong.com/warranty

Weight; Square Feet/Carton

741 – 0.75 lbs/SF; 40 SF/ctn
746 – 0.90 lbs/SF; 40 SF/ctn

Minimum Order Quantity

1 carton